

6121 Baker Road,
Suite 108
Minnetonka, MN 55345

www.chtechnology.com



Phone (952) 933-6190
Fax (952) 933-6223

1-800-274-4284

Thank you for downloading this document from C&H Technology, Inc.

Please contact the C&H Technology team for the following questions -

Technical

Application

Assembly

Availability

Pricing

Phone – 1-800-274-4284

E-Mail – sales@chtechnology.com

GTO Snubber Capacitors, Oil Impregnated

PART NO. GTO 4500-6.0P
ART. NO. 10726

NOMINAL RATINGS

Capacitance/Tolerance	CN	6 μ F \pm 5%
Rated voltage	UN	4500V
Rated DC voltage	U _{dc}	3300VDC
Rated RMS voltage	U _{rms}	1400VAC
Peak voltage period.	U _s	4500VDC
Peak voltage not period.	U _{smax}	4900VDC

Voltage raise	du/dt	1200V/us
Rated current	I _n	160A
Peak current	I _s	7200A

Inductance	L _s	< 15nH
Loss factor diel.	tan δ	< 2.0*10 ⁻⁴
Loss factor 50Hz	tan δ	< 2.0*10 ⁻⁴
1kHz	tan δ	< 4.0*10 ⁻⁴

ROUTINE TESTS

Test voltage terminal/terminal	UT/T	7300VDC, 10s
--------------------------------	------	--------------

OPERATING TEMPERATURE

Minimum ambient temperature	T _{a min}	- 25°C
Maximum ambient temperature	T _{a max}	60°C
Minimum casing temperature	T _{c min}	- 25°C
Maximum casing temperature	T _{c max}	70°C

The list below contains our standard program for GTO capacitors with a rated voltage of 4500V. All parameters not mentioned below are in accordance with this data sheet.

Type	C μ F	I _s A	Dimensions \varnothing d x h (mm)	Weight kg
GTO 4500 - 0.25 P	0.25	300	92 x 91	0.59
GTO 4500 - 0.50 P	0.50	600	92 x 91	0.59
GTO 4500 - 1.00 P	1.00	1200	92 x 91	0.59
GTO 4500 - 2.00 P	2.00	2400	92 x 91	0.59
GTO 4500 - 3.00 P	3.00	3600	92 x 141	0.92
GTO 4500 - 4.00 P	4.00	4800	92 x 141	0.92
GTO 4500 - 5.00 P	5.00	6000	92 x 141	0.92
GTO 4500 - 6.00 P	6.00	7200	92 x 161	1.05
GTO 4500 - 7.00 P	7.00	8400	92 x 181	1.18

- Other values upon request.
- Above capacitors types are usually available ex stock.
- All other types have to be manufactured in accordance with specific orders, however certain minimum order quantities may be requested depending on the capacitor type.
- The dimensions may be changed due to technical advances without notice.

STORAGE TEMPERATURE

Minimum temperature	T _{min}	- 50°C
Maximum temperature	T _{max}	+ 85°C

TECHNOLOGY

Dielectric	Polypropylene film non self-healing
Impregnation	oil, NON PCB

BUSHING

Internal thread	M8 depth 15mm
Air distance	217mm
Creepage distance	217mm

DESIGN DATA

Diameter	91mm
Height	161mm
Drawing	20-B-043
Weight	1.2kg
Casing material	Lathene

Mounting	every position
----------	----------------

LIFE EXPECTANCY	> 100000 Std
------------------------	--------------

FAILURE RATE	300 FIT
---------------------	---------

DIMENSIONS
